

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version      Revision Date:      SDS Number:      Date of last issue: 01/29/2016  
3.0            03/19/2016            953200-00005            Date of first issue: 02/09/2015

---

**SECTION 1. IDENTIFICATION**

Product name : DOW CORNING(R) 340 HEAT SINK COMPOUND

Product code : 000000000001015443, 000000000001015443

**Manufacturer or supplier's details**

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road  
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Heat transfer agents

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Silicone compound

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Zinc oxide	1314-13-2	>= 50 - < 70

---

**SECTION 4. FIRST AID MEASURES**

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version      Revision Date:      SDS Number:      Date of last issue: 01/29/2016  
3.0            03/19/2016            953200-00005      Date of first issue: 02/09/2015

---

- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.
- 

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Metal oxides  
Carbon oxides  
Silicon oxides  
Formaldehyde
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.
-

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**Version  
3.0Revision Date:  
03/19/2016SDS Number:  
953200-00005Date of last issue: 01/29/2016  
Date of first issue: 02/09/2015

Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Zinc oxide	1314-13-2	TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH
		STEL (Respirable fraction)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Dust)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Fumes)	5 mg/m <sup>3</sup>	NIOSH REL

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version      Revision Date:      SDS Number:      Date of last issue: 01/29/2016  
 3.0      03/19/2016      953200-00005      Date of first issue: 02/09/2015

		ST (Fumes)	10 mg/m <sup>3</sup>	NIOSH REL
		C (Dust)	15 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Fumes)	5 mg/m <sup>3</sup>	OSHA Z-1

- Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.

**Personal protective equipment**

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

- Remarks : Wash hands before breaks and at the end of workday.

- Eye protection : Wear the following personal protective equipment:  
 Safety glasses

- Skin and body protection : Skin should be washed after contact.

- Hygiene measures** : Ensure that eye flushing systems and safety showers are located close to the working place.  
 When using do not eat, drink or smoke.  
 Wash contaminated clothing before re-use.  
 These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : paste  
 Color : white  
 Odor : none

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version 3.0	Revision Date: 03/19/2016	SDS Number: 953200-00005	Date of last issue: 01/29/2016 Date of first issue: 02/09/2015
----------------	------------------------------	-----------------------------	---

---

Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	No data available
Relative density	:	2.0
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Use at elevated temperatures may form highly hazardous compounds.

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version 3.0	Revision Date: 03/19/2016	SDS Number: 953200-00005	Date of last issue: 01/29/2016 Date of first issue: 02/09/2015
----------------	------------------------------	-----------------------------	---

Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

**Hazardous decomposition products**

Thermal decomposition : Formaldehyde

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Ingredients:****Zinc oxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

**Skin corrosion/irritation**

Not classified based on available information.

**Ingredients:****Zinc oxide:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Ingredients:****Zinc oxide:**

Species: Rabbit  
Result: No eye irritation

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**Version  
3.0Revision Date:  
03/19/2016SDS Number:  
953200-00005Date of last issue: 01/29/2016  
Date of first issue: 02/09/2015

Method: OECD Test Guideline 405

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:****Zinc oxide:**

Test Type: Maximization Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:****Zinc oxide:**

Genotoxicity in vitro

: Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 474  
Result: negative**Carcinogenicity**

Not classified based on available information.

**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**Version  
3.0Revision Date:  
03/19/2016SDS Number:  
953200-00005Date of last issue: 01/29/2016  
Date of first issue: 02/09/2015**Ingredients:****Zinc oxide:**

- Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 416  
Result: negative
- Effects on fetal development : Test Type: Embryo-fetal development  
Species: Hamster  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Ingredients:****Zinc oxide:**

- Routes of exposure: inhalation (dust/mist/fume)  
Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**Repeated dose toxicity****Ingredients:****Zinc oxide:**

- Species: Rat  
NOAEL: 1.5 mg/m<sup>3</sup>  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 3 Months  
Method: OECD Test Guideline 413

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Zinc oxide:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 330 - 780 µg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

## DOW CORNING(R) 340 HEAT SINK COMPOUND

Version      Revision Date:      SDS Number:      Date of last issue: 01/29/2016  
 3.0            03/19/2016            953200-00005      Date of first issue: 02/09/2015

---

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 6.9 - 16.2 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Selenastrum capricornutum (green algae)): 136 µg/l Exposure time: 72 h Method: OECD Test Guideline 201
		NOEC (Selenastrum capricornutum (green algae)): 24 µg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	:	1
Toxicity to fish (Chronic toxicity)	:	NOEC (Oncorhynchus mykiss (rainbow trout)): 199 µg/l Exposure time: 30 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 37 µg/l Exposure time: 21 d Remarks: Based on data from similar materials
M-Factor (Chronic aquatic toxicity)	:	1
Toxicity to bacteria	:	EC50: 5.2 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

### Persistence and degradability

No data available

### Bioaccumulative potential

#### Ingredients:

##### Zinc oxide:

Bioaccumulation	:	Species: Fish Bioconcentration factor (BCF): 177
-----------------	---	---

### Mobility in soil

No data available

### Other adverse effects

No data available

## DOW CORNING(R) 340 HEAT SINK COMPOUND

Version      Revision Date:      SDS Number:      Date of last issue: 01/29/2016  
 3.0            03/19/2016            953200-00005      Date of first issue: 02/09/2015

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.
- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulation

##### UNRTDG

- UN number : UN 3077
- Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(Zinc oxide)
- Class : 9
- Packing group : III
- Labels : 9

##### IATA-DGR

- UN/ID No. : UN 3077
- Proper shipping name : Environmentally hazardous substance, solid, n.o.s.  
(Zinc oxide)
- Class : 9
- Packing group : III
- Labels : Miscellaneous
- Packing instruction (cargo aircraft) : 956
- Packing instruction (passenger aircraft) : 956

##### IMDG-Code

- UN number : UN 3077
- Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(Zinc oxide)
- Class : 9
- Packing group : III
- Labels : 9
- EmS Code : F-A, S-F
- Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version 3.0	Revision Date: 03/19/2016	SDS Number: 953200-00005	Date of last issue: 01/29/2016 Date of first issue: 02/09/2015
----------------	------------------------------	-----------------------------	---

---

**49 CFR**

UN/ID/NA number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S. (Zinc oxide)
Class	:	9
Packing group	:	III
Labels	:	CLASS 9
ERG Code	:	171
Marine pollutant	:	yes (Zinc oxide)
Remarks	:	Above applies only to containers over 119 gallons or 450 liters., Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

---

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc oxide	1314-13-2	69 %
------------	-----------	------

**US State Regulations****Pennsylvania Right To Know**

Zinc oxide	1314-13-2
------------	-----------

Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9
---	------------

**California Prop. 65** This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**California List of Hazardous Substances**

II	Zinc oxide	1314-13-2
----	------------	-----------

**California Permissible Exposure Limits for Chemical Contaminants**

II	Zinc oxide	1314-13-2
----	------------	-----------

**The ingredients of this product are reported in the following inventories:**


**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version 3.0 Revision Date: 03/19/2016 SDS Number: 953200-00005 Date of last issue: 01/29/2016  
Date of first issue: 02/09/2015

NZIoC	All ingredients listed or exempt.
TSCA	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
AICS	All ingredients listed or exempt.
IECSC	All ingredients listed or exempt.
ENCS/ISHL	All components are listed on ENCS/ISHL or exempted from inventory listing.
KECI	All ingredients listed, exempt or notified.
PICCS	All ingredients listed or exempt.
DSL	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
REACH	For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
TCSI	All ingredients listed or exempt.

**SECTION 16. OTHER INFORMATION****Further information****NFPA:**

Flammability

**HMIS III:**

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**

Version 3.0	Revision Date: 03/19/2016	SDS Number: 953200-00005	Date of last issue: 01/29/2016 Date of first issue: 02/09/2015
----------------	------------------------------	-----------------------------	---

OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/19/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

**DOW CORNING(R) 340 HEAT SINK  
COMPOUND**Version  
3.0Revision Date:  
03/19/2016SDS Number:  
953200-00005Date of last issue: 01/29/2016  
Date of first issue: 02/09/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8