



SAFETY DATA SHEET

Issuing Date 01-Oct-2014

Revision Date 01-Oct-2014

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Hi Purity Action Marker, all colors

Other means of identification

Part Number 33729, 44729 (White), 44916 (Yellow), 33404, 44404 (Black), 33301, 44301 (Red), 44534 (Blue)

Formula Code P729 (White), Z916 (Yellow), Q404 (Black), T301 (Red), Z534 (Blue)

UN-Number UN1263

Synonyms Hi Purity AM 33- Fine, and 44-Medium

Recommended use of the chemical and restrictions on use

Recommended Use Solvent based marker

Uses advised against No information available

Supplier's details

Supplier Address
ITW PRO BRANDS
805 E. Old 56 Highway
Olathe, KS 66061
TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone Number 800-535-5053 Infotrac

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3

Aspiration Toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements**Emergency Overview**

Signal Word Hazard Statements	Danger	
<ul style="list-style-type: none"> • May be harmful if inhaled • Causes skin irritation • Causes serious eye irritation • May cause genetic defects • Suspected of causing cancer • Suspected of damaging fertility or the unborn child • May cause respiratory irritation. May cause drowsiness or dizziness • May be fatal if swallowed and enters airways • Flammable liquid and vapor. 		
		
Appearance Opaque, Varies, Thin viscosity,	Physical State Liquid.	Odor Aromatic

Precautionary Statements**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wash face, hands and any exposed skin thoroughly after handling.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep cool.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- If skin irritation occurs: Get medical advice/attention.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Wash contaminated clothing before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Fire

- In case of fire: Use CO₂, dry chemical, or foam for extinction.

Spills and Leaks

- None

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

Hi Purity AM 33- Fine, and 44-Medium

Chemical Name	CAS-No	Weight %	Trade secret
Diacetone alcohol	123-42-2	30-60	*
Titanium dioxide	13463-67-7	30-60	*
Petroleum naphtha, light aromatic	64742-95-6	15-40	*
1,2,4 Trimethylbenzene	95-63-6	15-40	*
Propylene glycol monomethyl ether	107-98-2	10-30	*
Xylene, mixed isomers	1330-20-7	10-30	*
1,3,5-Trimethylbenzene	108-67-8	3 -7	*
Ethylbenzene	100-41-4	3 -7	*
Methyl pyrrolidone	872-50-4	1-5	*
Cumene	98-82-8	1-5	*
Naphtha (petroleum), heavy alkylate	64741-65-7	1-5	*
Stoddard solvent	8052-41-3	1-5	*
2-Ethylhexanoic acid	149-57-5	0.1-1	*
Toluene	108-88-3	0.1-1	*

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

4. FIRST AID MEASURES

Description of necessary first-aid measures**Eye Contact**

Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact

Wash skin with soap and water. If skin irritation persists, call a physician.

Inhalation

Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary
Protection of First-aiders	Use personal protective equipment. Remove all sources of ignition.

Most important symptoms/effects, acute and delayed**Most Important Symptoms/Effects** No information available.**Indication of immediate medical attention and special treatment needed, if necessary****Notes to Physician** Treat symptomatically.**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**Carbon dioxide (CO₂). Foam. Dry chemical.**Unsuitable Extinguishing Media** No information available.**Specific Hazards Arising from the Chemical**

Flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition

Explosion Data**Sensitivity to Mechanical Impact**

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Environmental Precautions**Environmental Precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Collect spillage. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

7. HANDLING AND STORAGE**Precautions for safe handling**

Handling Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Conditions for safe storage, including any incompatibilities

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

Incompatible Products Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m ³	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Propylene glycol monomethyl ether 107-98-2	STEL: 150 ppm TWA: 100 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m ³	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³
Xylene, mixed isomers 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Silicon dioxide 7631-86-9	10 mg/m ³	20 mppcf TWA; ((80)/(%) SiO ₂) mg/m ³)	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
1,3,5-Trimethylbenzene 108-67-8	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m ³ respirable fraction	-	-
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
2-Ethylhexanoic acid 149-57-5	TWA: 5 mg/m ³ inhalable fraction and vapor	-	-

Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
---------------------	-------------	--	---

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash goggles.

Skin and Body Protection Chemical resistant gloves. Risk of contact: Boots. Apron.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Appearance	Opaque, Varies Thin viscosity,
Odor	Aromatic	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	120-170 °C / 248-338 °F	None known
Flash Point	31.67 - 42.22 °C / 89 - 108 °F	None known
Evaporation rate	< 1 (BuAc = 1)	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available 12.6	
lower flammability limit	No data available 1.0	
Vapor Pressure	No data available	None known
Vapor Density	> 1 (air = 1)	None known
Specific Gravity	> 1 @ 70°F	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Flammable; may be ignited by heat, sparks or flames.

Explosive Properties No data available
Oxidizing Properties No data available

Other information

VOC Content (%)	Z534 Blue: 67.72% P729 White: 37.89% T301 Red: 71.9% Z916 Yellow: 36.43%
VOC (g/l)	Q404 Black: 84.91% Z534 Blue: 719 g/L P729 White: 465 g/L T301 Red: 669 g/L Z916 Yellow: 447 g/L Q404 Black: 816 g/L

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Incompatible products.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products

Carbon oxides. Smoke Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

May be harmful by inhalation. May cause irritation of respiratory tract. May cause drowsiness and dizziness.

Eye Contact

Irritating to eyes. Causes serious eye irritation.

Skin Contact

Irritating to skin. Causes skin irritation.

Ingestion

May be fatal if swallowed and enters airways.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Diacetone alcohol	= 4 g/kg (Rat)	= 13500 mg/kg (Rabbit)	-
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
1,2,4 Trimethylbenzene	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Propylene glycol monomethyl ether	= 5200 mg/kg (Rat)	= 13000 mg/kg (Rabbit)	> 24 mg/L (Rat) 1 h = 54.6 mg/L (Rat) 4 h
Xylene, mixed isomers	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Silicon dioxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat) 4 h

1,3,5-Trimethylbenzene	= 5000 mg/kg (Rat)	-	= 24 g/m ³ (Rat) 4 h
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Aluminum hydroxide	> 5000 mg/kg (Rat)	-	-
Methyl pyrrolidone	= 3598 mg/kg (Rat)	= 2500 mg/kg (Rat) > 5000 mg/kg (Rabbit)	= 3.1 mg/L (Rat) 4 h
Cumene	= 1400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 39000 mg/m ³ (Rat) 4 h
2-Ethylhexanoic acid	= 3 g/kg (Rat)	= 1260 mg/kg (Rabbit) > 2000 mg/kg (Rat)	-
Toluene	>5580 mg/kg (Rat)	12124 mg/kg (Rat) 8390 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available.

Mutagenic Effects May cause genetic defects.

Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Xylene, mixed isomers		Group 3		
Ethylbenzene	A3	Group 2B		X
Cumene		Group 2B		
Toluene		Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity

STOT - single exposure

STOT - repeated exposure

Chronic Toxicity

Product is or contains a chemical which is a known or suspected reproductive hazard.

No information available.

No information available.

Avoid repeated exposure. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. Contains a known or suspected reproductive toxin. May cause adverse liver effects. May cause adverse effects on the bone marrow and blood-forming system. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects

Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood. Lungs.

Aspiration Hazard

May be fatal if swallowed and enters airways

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 5082 mg/kg; Acute toxicity estimate

LD50 Dermal 5892 mg/kg; Acute toxicity estimate

Inhalation

dust/mist 9.03 mg/L; Acute toxicity estimate

Vapor 23 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Diacetone alcohol 123-42-2		LC50 96 h: = 420 mg/L static (Lepomis macrochirus) LC50 96 h: = 420 mg/L (Lepomis macrochirus)		EC50 24 h: = 8750 mg/L (Daphnia magna)
Petroleum naphtha, light aromatic 64742-95-6		LC50 96 h: = 9.22 mg/L (Oncorhynchus mykiss)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
1,2,4 Trimethylbenzene 95-63-6		LC50 96 h: 7.19 - 8.28 mg/L flow-through (Pimephales promelas) LC50 96 h: = 7.72 mg/L flow-through (Pimephales promelas)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
Propylene glycol monomethyl ether 107-98-2		LC50 96 h: 4600-10000 mg/L static (Leuciscus idus) LC50 96 h: = 20.8 g/L static (Pimephales promelas)		EC50 48 h: = 23300 mg/L (Daphnia magna)
Xylene, mixed isomers 1330-20-7	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)		EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)
1,3,5-Trimethylbenzene 108-67-8		LC50 96 h: = 3.48 mg/L (Pimephales promelas)		EC50 24 h: = 50 mg/L (Daphnia magna)
Ethylbenzene 100-41-4	EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0 - 18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: 7.55 - 11 mg/L flow-through (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: 9.1 - 15.6 mg/L static (Pimephales promelas) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)
Methyl pyrrolidone 872-50-4	EC50 72 h: > 500 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 832 mg/L static (Lepomis macrochirus) LC50 96 h: = 4000 mg/L static (Leuciscus idus) LC50 96 h: = 1072 mg/L static (Pimephales promelas) LC50 96 h: = 1400 mg/L static (Poecilia reticulata)		EC50 48 h: = 4897 mg/L (Daphnia magna)

Cumene 98-82-8	EC50 72 h: = 2.6 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 6.04-6.61 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.7 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 4.8 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 5.1 mg/L semi-static (Poecilia reticulata)	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	EC50 48 h: 7.9 - 14.1 mg/L Static (Daphnia magna) EC50 48 h: = 0.6 mg/L (Daphnia magna)
Naphtha (petroleum), heavy alkylate 64741-65-7	EC50 72 h: = 30000 mg/L (Pseudokirchneriella subcapitata)			LC50 48 h: = 2 mg/L (Mysidopsis bahia)
2-Ethylhexanoic acid 149-57-5	EC50 96 h: = 41 mg/L (Desmodesmus subspicatus) EC50 72 h: = 61 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 70 mg/L (Pimephales promelas)	EC50 = 110 mg/L 17 h EC50 = 670 mg/L 30 min	EC50 48 h: = 85.4 mg/L (Daphnia magna)
Toluene 108-88-3	EC50: >433 mg/L Pseudokirchneriella subcapitata 96 h EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static	LC50: 15.22-19.05 mg/L Pimephales promelas 96 h flow-through LC50: 12.6 mg/L Pimephales promelas 96 h static LC50: 5.89-7.81 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 14.1-17.16 mg/L Oncorhynchus mykiss 96 h static LC50: 5.8 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 11.0-15.0 mg/L Lepomis macrochirus 96 h static LC50: 54 mg/L Oryzias latipes 96 h static LC50: 28.2 mg/L Poecilia reticulata 96 h semi-static LC50: 50.87-70.34 mg/L Poecilia reticulata 96 h static	EC50 = 19.7 mg/L 30 min	EC50 48 h: 5.46 - 9.83 mg/L Static (Daphnia magna) EC50 48 h: = 11.5 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Diacetone alcohol	1.03
1,2,4 Trimethylbenzene	3.63
Propylene glycol monomethyl ether	-0.437
Xylene, mixed isomers	2.77 - 3.15
Ethylbenzene	3.118
Methyl pyrrolidone	-0.46
Cumene	3.55
2-Ethylhexanoic acid	2.7
Toluene	2.65

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number
 D001
 U012
 U055
 U220
 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene, mixed isomers - 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene - 100-41-4		Included in waste stream: F039		
Cumene - 98-82-8				U055
Toluene - 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Component	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3 (0.1-1)			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Xylene, mixed isomers	Toxic Ignitable
Ethylbenzene	Toxic Ignitable
Cumene	Toxic Ignitable
Toluene	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III
Description UN1263, Paint, 3, III
Emergency Response Guide Number 128

TDG

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III
Description UN1263, Paint, 3, III

MEX

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Description	UN1263, Paint, 3, III

ICAO

UN-Number	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	III
Description	UN1263, Paint, 3, III

IATA

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
ERG Code	3L
Description	UN1263, Paint, 3, III

IMDG/IMO

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
EmS No.	F-E, S-E
Marine Pollutant	Product is a marine pollutant according to the criteria set by IMDG/IMO
Description	UN1263, Paint, 3, III, (42.22°C c.c.)

RID

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1263, Paint, 3, III

ADR

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Tunnel Restriction Code	(D/E)
Description	UN1263, Paint, 3, III, (D/E)

ADN

Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Special Provisions	163, 640E, 650
Description	UN1263, Paint, 3, III
Limited Quantity	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene	95-63-6	15-40	1.0
Xylene, mixed isomers	1330-20-7	10-30	1.0
Ethylbenzene	100-41-4	3-7	0.1
Methyl pyrrolidone	872-50-4	1-5	1.0
Cumene	98-82-8	1-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene, mixed isomers	100 lb			X
Ethylbenzene	1000 lb	X	X	X
Toluene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene, mixed isomers	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Ethylbenzene	100-41-4	Carcinogen
Methyl pyrrolidone	872-50-4	Developmental
Cumene	98-82-8	Carcinogen
2-Ethylhexanoic acid	149-57-5	Developmental
Toluene	108-88-3	Developmental
Aniline	62-53-3	Carcinogen
Quartz	14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island

Diacetone alcohol	X	X	X		X
Titanium dioxide		X			X
1,2,4 Trimethylbenzene	X	X	X	X	X
Propylene glycol monomethyl ether	X	X	X		X
C.I. Pigment Blue 28	X		X	X	
Xylene, mixed isomers	X	X	X	X	X
1,3,5-Trimethylbenzene	X	X	X	X	X
Ethylbenzene	X	X	X	X	X
Methyl pyrrolidone	X	X	X		
Cumene	X	X	X	X	X
Diethylbenzene	X				
Stoddard solvent	X	X	X		X
Toluene	X	X	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal Protection X

*Indicates a chronic health hazard.

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 01-Oct-2014
Revision Date 01-Oct-2014
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet