## DEL PAINT CORP -- F5001 PAINT THINNER -- 8010-00F051050

Product ID:F5001 PAINT THINNER MSDS Date:10/23/1996 FSC:8010 NIIN:00F051050 MSDS Number: CCZSW === Responsible Party === Company Name: DEL PAINT CORP Address:3105 E RENO AVE City:OKLAHOMA CITY State:OK ZIP:73117-6699 Country:US Info Phone Num:405-672-1431/800-866-6823 Emergency Phone Num:800-866-6823/405-672-1431 CAGE: EO523 === Contractor Identification === Company Name: DEL PAINT CORP Address:3105 E RENO AVE City:OKLAHOMA CITY State:OK ZIP:73117-6699 Country:US Phone: 405-672-1431/800-866-6823 CAGE:E0523 Company Name: DEL PAINT MFG Address:3105 EAST RENO Box:City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone: 405-672-1431 CAGE: 39934 Ingred Name:STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS \*96-4\* CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 100% Other REC Limits:525 MG/CUM OSHA PEL:400 PPM ACGIH TLV:100 PPM Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO IARC:NO OSHA:NO Reports of Carcinogenicity:NTP:NO Health Hazards Acute and Chronic: INHALATION: IRRITATION TO THE MUCOUS MEMBRANES OF THE LUNG. Explanation of Carcinogenicity:NONE Effects of Overexposure: INTOXICATION, NARCOTIC, IRRITATION, REDNESS, PAIN, LABORED BREATHING, DULLNESS, DROWSINESS, ABDOMINAL PAIN,

NAUSEA. Medical Cond Aggravated by Exposure: DISEASES OF THE RESPIRATORY SYSTEM. First Aid:SKIN: SHOWER/RINSE W/PLENTY OF WATER. EYES: RINSE W/COPIOUS AMOUNTS OF WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NECESSARY. INGESTION: RINSE MOUTH & DRINK PLENTY OF WATER. DON'T INDUCE VOMIT ING. OBTAIN MEDICAL ATTENTION IN ALL CASES. Flash Point Method:TCC Flash Point:100F Lower Limits:0.9 Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL Fire Fighting Procedures: USE SCBA W/A FULL FACEPIECE OPERATED IN PRESSURE DEMAND/OTHER POSITIVE MODE. Unusual Fire/Explosion Hazard: VAPORS ARE > THAN AIR & TRAVEL ALONG THE GROUND & IGNITE BY OTHER REMOTE IGNITION SOURCES. COMBUSTIBLE. Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT/OTHER ABSORBENT MATERIAL & TRANSFER TO HOOD. Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY FROM FOOD PRODUCTS. KEEP AWAY FROM SPARKS, FIRES & REMOTE IGNITION SOURCES. Respiratory Protection: IF TLV IS EXCEEDED, A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED. OSHA ALSO PERMITS OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS. Ventilation: REOUIRED SUFFICIENT TO MAINTAIN EXPOSURE BELOW TLVS. Protective Gloves:RESISTANT/BUNA-N Eye Protection: SPLASH GOGGLES/SAFETY GLASSES Other Protective Equipment: IMPERVIOUS CLOTHING & BOOTS. Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS & FACE BEFORE EATING. Supplemental Safety and Health Boiling Pt:B.P. Text: 305-396F Vapor Pres:2 Vapor Density:>1 Evaporation Rate & Reference:SLOWER THAN ETHER Percent Volatiles by Volume:100 Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, WATER.

Stability Condition to Avoid:HEATED SURFACES, OPEN FLAMES/IGNITION SOURCES. Hazardous Decomposition Products:COMBUSTION: CO2

Waste Disposal Methods:DISPOSE OF TO A LICENSED LANDFILL IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.