

## SAFETY DATA SHEET

### Section 1: Product and Company Identification

**Product Name:** PRO-MAX® Liquid Paint Marker

**Product Code:** 90900 (white), 90901 (yellow), 90902 (red), 90903 (black), 90904 (orange), 90905 (blue).

**Product Use:** Marker for metal, suitable for wood, glass, plastic rubber and more with marking range -50°F to 150°F (-46°C to 66°C).

**Supplier:** LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL.  
60007-5746  
E-mail Contact: customer\_service@laco.com

**Phone Number:** (847) 956-7600  
**Fax:** (847) 956-9885  
**24-hour Emergency:** CHEMTREC: (800) 424-9300

### Section 2: Hazards Identification

#### 2.1 Classification of the substance or mixture according to GHS Classifications (UNECE 3<sup>rd</sup> Revised Edition):

Not classified as a hazardous chemical.

#### 2.2 Label elements:

No hazard classifications.

#### 2.3 Other hazards:

The paint inside the marker is a flammable liquid. Exposure to vapors from misuse of the product may cause drowsiness and dizziness. Exposure to hazardous substances is not expected when handling this product for its intended use.

#### 2.4 Other hazard classifications:

Marker meets the definition of an "article".

USA: This article is not considered a hazardous chemical by the OSHA Hazard Communication Standard 29 CFR 1910.1200 (2012).

Canada: This article is not a controlled product under WHMIS.

European Union (EU): This article is not classified as hazardous according to CLP Regulation (EC) No 1272/2008.

### Section 3: Composition / Information on Ingredients

| Chemical Name        | CAS No.  | Wt. %   | GHS Classifications<br>according to UNECE 3 <sup>rd</sup> Revised Edition |
|----------------------|----------|---------|---------------------------------------------------------------------------|
| 1-methoxypropan-2-ol | 107-98-2 | 60 - 81 | Flam. Liq. 3; H226 & STOT SE 3; H336                                      |

### Section 4: First Aid Measures

#### 4.1 Description of first aid measures:

**Inhalation:** If symptoms are experienced, remove source of contamination or have victim move to fresh air. Obtain medical advice.

**Eye Contact:** No effects expected. If contact with the paint occurs, flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelids open. If irritation persists, obtain medical attention.

**Skin Contact:** No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

**Ingestion:** No health effects expected. If swallowed, do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Obtain medical advice or call a POISON CENTER or doctor/physician.

## SAFETY DATA SHEET

### Section 4: First Aid Measures

#### 4.2 Most important symptoms and effects, both acute and delayed:

Exposure to hazardous substances is not expected when handling this product for its intended use.

Exposure to vapors from the paint may result from misuse of the marker. Breathing vapors may cause drowsiness and dizziness.

### Section 5: Fire Fighting Measures

#### 5.1 Extinguishing media:

For small fires use dry chemicals, carbon dioxide, appropriate foam, or inert gas (nitrogen).

For large fires use appropriate foam, water fog, or water spray. Water can be used to cool fire-exposed containers.

#### 5.2 Special hazards arising from the substance:

Markers contain a small volume of paint which is a flammable liquid, category 3. Flashpoint 31°C (88°F).

#### 5.3 Advice for firefighters:

If involved in a fire, combustion may produce toxic and irritating fumes and gases including carbon dioxide, carbon monoxide and/or unburned hydrocarbons.

As for any fire, evacuate the area and fight the fire from a safe distance. Firefighters must wear full protective clothing and positive pressure self-contained breathing apparatus.

### Section 6: Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures:

If large volumes of paint are released shut off or extinguish all sources of ignition. Do not breathe vapors. Ventilate the area.

#### 6.2 Environmental precautions:

Prevent the spilled liquid from entering sewers or waterways.

#### 6.3 Methods and material for containment and cleaning up:

Stop the spill if it is safe to do so.

Absorb any spilled liquid using dry earth, sand or non-combustible absorbent material and transfer to appropriate covered and labeled waste containers.

#### 6.4 Additional Information:

See Section 8 for information on selection of personal protective equipment.

See Section 13 for information on disposal of spilled product and contaminated absorbents.

### Section 7: Handling and Storage

#### 7.1 Precautions for safe handling:

Keep out of reach of children.

Do not use near hot surfaces or flames.

#### 7.2 Conditions for safe storage, including any incompatibilities:

Store away from ignition sources, extreme heat and out of direct sunlight. Keep markers closed when not in use.

### Section 8: Exposure Controls/Personal Protection

#### 8.1 Control parameters:

##### Occupational Exposure Limits:

Measurable airborne concentrations of the component substances, listed in Section 3, are not expected when the markers are used for their intended purpose. Consult local authorities for acceptable exposure limits.

#### 8.2 Exposure controls:

##### **Engineering Controls:**

General ventilation is normally adequate.

**Personal Protection:** Workers must comply with the Personal Protective Equipment requirements of the workplace in which this product is handled.

## SAFETY DATA SHEET

### Section 8: Exposure Controls/Personal Protection, continued

**Eye/Face Protection:** Not required for normal use. In case of accidental release of large quantities of paint, wear goggles.

**Skin Protection:** Not required for normal use. In case of accidental release of large quantities of paint, wear gloves.

**Respiratory Protection:** Not required for normal use.

**Other Protection:** Avoid breathing vapors. Keep out of reach of children.

### Section 9: Physical and Chemical Properties

#### 9.1 Information on basic physical and chemical properties:

|                                                      |                                                 |
|------------------------------------------------------|-------------------------------------------------|
| <b>Appearance:</b>                                   | Solid, containing liquid, colored paint.        |
| <b>Odor:</b>                                         | Mild odor of ether.                             |
| <b>Odor threshold:</b>                               | Not available                                   |
| <b>pH:</b>                                           | Not available                                   |
| <b>Melting point/freezing point:</b>                 | Not available                                   |
| <b>Initial boiling point and boiling range:</b>      | 120°C (248°F) (paint)                           |
| <b>Flash point:</b>                                  | 31°C (88°F) for 1-methoxypropan-2-ol DIN EN 456 |
| <b>Flammability</b>                                  | Paint contained in marker is a flammable liquid |
| <b>Auto-ignition temperature:</b>                    | 287°C (594°F) for 1-methoxypropan-2-ol          |
| <b>Upper/lower flammability or explosive limits:</b> | Lower: 1.7 vol. %. Upper: 11.5 vol. %           |
| <b>Explosive properties:</b>                         | Not available                                   |
| <b>Oxidizing properties:</b>                         | Not available                                   |
| <b>Sensitivity to mechanical impact:</b>             | Not available                                   |
| <b>Sensitivity to static discharge:</b>              | Not available                                   |
| <b>Vapor pressure:</b>                               | 11.8 for 1-methoxypropan-2-ol                   |
| <b>Evaporation rate:</b>                             | <1 (n-butyl acetate = 1)                        |
| <b>Vapor density:</b>                                | 3.12 for 1-methoxypropan-2-ol                   |
| <b>Relative density:</b>                             | 0.98 – 1.2 g/L @ 20°C (paint)                   |
| <b>Solubility (is):</b>                              | Insoluble in water.                             |
| <b>Partition coefficient (n-octane/water):</b>       | Not available                                   |
| <b>Decomposition temperature:</b>                    | Not available                                   |
| <b>Viscosity:</b>                                    | Not available                                   |
| <b>VOC Content:</b>                                  | 65 – 80%                                        |

### Section 10: Stability and Reactivity

#### 10.1 Reactivity:

Not classified for reactivity hazards.

#### 10.2 Chemical Stability:

Stable at normal ambient and anticipated storage and handling conditions of temperature and pressure.

#### 10.3 Possibility of Hazardous Reactions:

None known

#### 10.4 Conditions to Avoid:

Do not use in conditions of heat or near open flames and sparks.

#### 10.5 Incompatible Materials:

Paint is incompatible with strong oxidizing agents, such as chlorine and oxygen.

#### 10.6 Hazardous Decomposition Products:

None known when used for its intended purpose. Combustion may produce irritating and/or toxic gases.

## SAFETY DATA SHEET

### Section 11: Toxicological Information

#### 11.1 Information on toxicological effects:

##### Acute Health Effects:

**Inhalation:** This product does not easily form a vapor; inhalation exposure is unlikely to occur, unless the marker is misused. Exposures to high vapor concentrations may cause drowsiness and dizziness.

**Ingestion:** Not an expected route of exposure with normal use of the product.

**Skin:** Repeated contact with the skin may cause irritation.

**Eye:** Not an expected route of exposure with normal use of the product. Direct contact with the liquid may cause irritation.

##### Acute Toxicity Data::

| <u>Component Substance</u> | <u>LD<sub>50</sub> Oral</u><br>(mg/kg) | <u>LD<sub>50</sub> Dermal</u><br>(mg/kg) | <u>LC<sub>50</sub> Inhalation</u><br>(4 hrs.)  |
|----------------------------|----------------------------------------|------------------------------------------|------------------------------------------------|
| 1-methoxypropan-2-ol       | 5 200 (rat)                            | 13 000 (rabbit)                          | 54.6 mg/L/4 hour (rat)<br>24 mg/L/1 hour (rat) |

##### Chronic Health Effects:

Data are not available.

##### Sensitization:

Not applicable

##### Neurological Effects:

Not applicable with normal use of the marker.

##### Genetic Effects:

Not applicable

##### Reproductive Effects:

Not applicable

##### Developmental Effects:

Not applicable with normal use of the marker.

##### Target Organ Effects:

Not applicable

##### Carcinogenicity:

This product does not contain any component that is considered a human carcinogen by IARC (International Agency for Research on Cancer), ACGIH (American Conference of Governmental Industrial Hygienists, OSHA or NTP (National Toxicology Program).

##### Medical Conditions Aggravated by Exposure:

Repeated skin contact may aggravate an existing dermatitis.

##### Interactions With Other Chemicals:

Data are not available.

### Section 12: Ecological Information

#### 12.1 Toxicity:

Germany Water Hazard Classes: 1-methoxypropan-2-ol ID Number 1597, hazard class 1 - low hazard to waters

#### 12.2 Persistence and degradability:

Not available

#### 12.3 Bioaccumulative potential:

Not available

#### 12.4 Mobility in soil:

Not available

## SAFETY DATA SHEET

### Section 13: Disposal Considerations

#### 13.1 Waste treatment methods:

Do NOT discard into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state/provincial and federal laws and regulations.

The conditions of use, storage and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, LA-CO Industries, Inc. does not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

### Section 14: Transport Information:

#### Transport Regulations:

**U.S. Hazardous Materials Regulation (DOT 49CFR):** This product conforms to 49 CFR 173.4 for domestic highway or rail transport only. Conforms to 49 CFR 173.4a Excepted quantity of Class 3 Flammable liquid.

**Canadian Transportation of Dangerous Goods (TDG):** Dangerous goods in excepted quantity.

**IMO Classification:** UN1263 , PAINT, Class 3, PGIII, FP 31°C, LTD QTY, EmS F-E, S-E

**ICAO/IATA Classification:** Dangerous goods in excepted quantity.

### Section 15: Regulatory Information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

##### USA

**OSHA:** Article, Non-Hazardous according to OSHA Hazard Communication Standard 29 CFR 1910.120 (2012).

##### SARA Title III

Sec. 302/304: None  
Sec. 311/312: Flammable  
Sec. 313: None  
CERCLA RQ: None

**California Prop 65:** Not applicable

**State Right-to-Know Lists :** 1-methoxypropan-2-ol can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, Massachusetts.

##### Canada

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the SDS contains all the information required by the *Controlled Products Regulations*.

##### WHMIS Classification:

Manufactured article, Not controlled

##### DSL Status:

All component substances listed on the DSL (Domestic Substances List).

##### NPRI Substances:

Not applicable

##### Europe

**OSHA:** This article is not classified as hazardous according to CLP Regulation (EC) No 1272/2008.

## SAFETY DATA SHEET

### Section 16: Other Information

**Text of H-phrases in Section 3:** H226: Flammable liquid and vapour.  
H336: May cause drowsiness or dizziness.

**Preparation Information:**

**Revision date:** February 13, 2013

**References and sources for data:**  
CCOHS – ChemInfo

**Legend to abbreviations:**

ACGIH – American Conference of Governmental Industrial Hygienists  
GHS- Globally Harmonised System for Classification and Labeling  
IARC – International Agency for Research on Cancer  
LD50- Median lethal dose; the dose causing 50 % lethality  
LEV- Local exhaust ventilation  
OSHA – United States, Occupational Safety and Health Administration  
STEL – Short term exposure limit  
TWA – Time weighted average  
TLV - Threshold Limit Value  
NTP – National Toxicology Program  
WHMIS – Canada, Workplace Hazardous Materials Information System

**Supplier Note:** The information contained herein is based on data available to us and is accurate and reliable to the best of our knowledge and belief. However, LA-CO Industries, Inc. makes no representations as to its completeness or accuracy. Information is supplied on condition that persons receiving such information will make their own determination as to its suitability for their purposes prior to use. In no event will LA-CO Industries, Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

**Prepared by:** LEHDER Environmental Services Limited (519) 336-4101  
www.lehder.com  
While LEHDER Environmental Services Limited believes that the data set forth herein is accurate, as of the date hereof, LEHDER makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation and verification.