

LymSat<sup>®</sup> (70/30 presaturated wipes) Preparation Date: 08/10/2011

Page 1 of 2

# MATERIAL SAFETY DATA SHEET

# 1. Chemical Product and Company Identification

Product Name: LymSat®

Part Numbers; 6-LS7030; 6-LS7030-585TL; 6-LS7030-685;

6-LS7030-685TL; 6-LS7030-917; 6-LS7030-99P-K40;

6-LS7030-9AP-N40; 6-LS7030-BBBK-K35; 6-LS7030-PC-24;

6-LS7030VS-99P-N30; 6-LS7030VS-99P-N40;

6-LS7030VS-BBP-K20; 6-LS7030VS-PC; 6E-LS7030;

6E-LS7030-685; 6E-LS7030VS-PC

Chemical Family: Blended isopropanol and deionized water.

LvmTech Scientific Company:

2255 Westover Road

Chicopee, Massachusetts 01022 USA

(413) 492-4111

Emergency Telephone: CHEMTREC (800) 424-9300

## 2. Composition/Information on Ingredients

**Chemical Name** Wt.% Range TLV Units Isopropyl Alcohol 70.0 400 ppm CAS #67-63-0

Deionized Water 30.0 None Assigned

CAS #7732-18-5

All components of this material are listed on the TSCA inventory.

#### 3. Hazard Identification

Emergency Overview: Fabric containing a flammable colorless liquid with an alcohol odor. Liquid will irritate eyes and skin under repeated or prolonged exposure. Product vapors can be moved by air currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources distant from product handling point. Keep away from children.

#### **Potential Health Effects**

Eyes: Vapor contact: Mild irritant. Liquid contact: Will irritate eyes with possible corneal injury. Persons wearing contact lenses should wear chemical protective safety glasses when exposed to this product.

**Skin:** For repeated contact: dry/chapped skin, risk of chronic dermatitis. **Ingestion:** Can cause depression of central nervous system, nausea, stomach cramps, vomiting, diarrhea.

**Inhalation:** At low concentration levels: may cause mild irritation to nose and throat. At high levels: headache, drowsiness and lassitude, loss of appetite, inability to concentrate.

Medical Conditions Aggravated by Exposure: Pre-existing disease of the heart, lungs, skin and eyes.

#### 4. First Aid Measures

Eyes: Immediately flush with water. Remove any contact lenses and continue flushing for 15 minutes, lifting eyelids occasionally until no evidence of the chemical remains. If irritation develops or persists call a physician.

Skin: Wash promptly with soap and water. Remove and wash contaminated clothing and shoes before reuse.

**Ingestion:** If conscious, immediately give 2-4 glasses of water and induce vomiting by touching finger to back of throat. Do not give stimulants. Never give anything by mouth to an unconscious person. Call a physician.

Inhalation: Remove to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Do not give Epinephrine. Call a physician.

Note to Attending Physician: There is no specific antidote to overexposure. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Immediate medical attention for acute overexposure is required.

## 5. Firefighting Measures

**Flash Point:** 53° F/12° C, Tag Closed Cup, ASTM-D-56. 63° F/17° C, Tag Open Cup, ASTM-D-1310.

Flammable Limits in Air: LEL/UEL: 2.0-12.7 (% by volume) Extinguishing Media: Use dry chemical, "alcohol" foam, CO2; water may be ineffective, but water should be used to keep fire exposed containers cool. If a spill or leak has not ignited, use water spray to disperse vapors and protect persons attempting to stop leak. Water may be used to flush spills away from exposures and to dilute spills to nonflammable mixtures.

Special Firefighting Procedures: Evacuate personnel. Wear self contained breathing apparatus (SCBA) and full protective equipment. Keep containers cool.

#### 6. Accidental Release Measures

Spill Or Leak: Evacuate area, absorb spilled liquid (if any) with commercial, nonflammable absorbent i.e. sand, vermiculite. Remove unprotected personnel. Protected personnel should remove ignition sources and shut off fire sources. Provide ventilation.

# 7. Handling and Storage

Avoid breathing vapors or mist. Use only with adequate ventilation. Avoid repeated or prolonged contact with eyes, skin or clothing. Wash thoroughly after handling. Do not store in direct sunlight. Store in cool dry place, away from heat, sparks or flames which may generate toxic decomposition products. Vapors are heavy and may concentrate in low poorly ventilated areas.

#### 8. Exposure Controls/Personal Protection

**Eve Protection:** Use chemical protective safety glasses.

**Protective Clothing:** Where there is potential for skin contact, use appropriate impervious gloves, apron, pants and jacket.

Exposure Guidelines: Applicable Exposure Limits:

Isopropyl Alcohol:

400 ppm TWA PEL (OSHA)

TLV (ACGIH) 400 ppm TWA, 500 ppm STEL

NFPA, NPCA-HIMIS RATING:

Health Flammability 3 Reactivity

Personal Protection rating to be supplied by user depending on use conditions.

#### 9. Physical and Chemical Properties

Physical Form: Clear colorless liquid saturated in fabric

sheets

Odor: Characteristic alcohol
Boiling Point: 82°C/180°F
pH: Not Determined
Solubility in Water: Complete

**Specific Gravity:**  $.87 \stackrel{\circ}{@} 15^{\circ}\text{C}/60^{\circ}\text{F}$ 

% Volatile by Weight: 100

**Vapor Pressure:**  $39 \text{mmHg} @ 20^{\circ} \text{ C} / 70^{\circ} \text{ F}$ 

Vapor Density (air=1) 1.82

#### 10. Reactivity

Chemical Stability: Material is stable.

Hazardous Polymerization: Will not occur.

**Incompatibilities:** Avoid concentrated nitric and sulfuric acids, strong oxidizers, aldehydes, acetyl chloride, halogens and

halogen compounds.

Decomposition Products: Burning may produce carbon monoxide

and/or carbon dioxide.

#### 11. Toxicological Information

**For Isopropanol:** Oral LD50 = 5,045 mg/kg in rats. Dermal LD50 = 12.8 gm/kg in rabbits. Inhalation LC50 =16,000 ppm/8 hour in rats.

**Carcinogenicity:** None of the components present in this product are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

# 12. Ecological Information

**Aquatic Toxicity:** 96 hour LC50 in fish: >100.0mg/L This material is not expected to be toxic to aquatic life.

#### 13. Disposal Considerations

**Waste Disposal:** Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial and Local regulations.

## 14. Transportation Information

#### Transport for LymSat Wipe Packaging:

**Ground Transport:** Consumer Commodity ORM-D

<u>Air Transport:</u> Solids Containing a Flammable Liquid N.O.S. (Isopropanol), UN3175, Class 4.1, Pkg. Group II, Pkg. Inst. 415

Hazard Label: Flammable Solid

## 15. Regulatory Information

Section 313 Supplier Information: This material contains the following toxic chemicals subject to the emergency reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40 CFR 372:

CAS # Chemical Name % by Weight 67-63-0 Isopropyl Alcohol 96.0% This information must be included in all MSDSs that are copied and distributed for this material.

#### Title III Hazard Communications Sections 311, 312

Acute Yes
Chronic Yes
Fire Yes
Reactivity No

#### 16. Other Information

The information contained herein is based on data available at this time and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Since information contained herein may be applied under conditions beyond our control, and with which we may be unfamiliar, no responsibility is assumed for the results of its use. The person receiving this information shall make his own determination of the suitability of the material for his particular use.