

[Click Here to Visit our Original Site](#)

[Home](#) | [How to Order](#) | [Contact](#) | [Site map](#) | [Privacy](#)

719-676-3928

[Live Chat!](#)[Email Us](#)

ESD Carpeting with permanent static control properties

Powerful Performance, Outstanding Value!

OUR PRODUCTS

- ESD Concrete Sealer
- ESD Tile
- ESD Carpet Tile
- ESD Sheet Floors
- ESD Epoxy Floor Paint
- ESD Wax, ETC
- ESD Matting
- ESD Constant Monitors
- Wrist & Heel Straps
- ESD Ionizers
- ESD Test Equipment
- ESD Smocks

● Our Most Popular ESD Floors

PURCHASE ON LINE

- [Shopping Cart!](#)

VIEW THIS SITE IN

- [Spanish](#)

EltraThane Material Safety Data Sheet

[\[Back\]](#) [Home](#) / [ESD Wax](#) / [ElectraThane](#) / [MSDS Sheet](#)

Eletrathane Flooring Sealant For Use With Electraguard

MSDS Sheet

SECTION I(Identity) - PN: E-Clean, Static Dissipative ESD Floor Cleaning Solution

Hazardous:	No
Health:	1
Flammability:	0
Reactivity:	0
Personal Protection:	B

Note

Most Hazardous:	4
-----------------	---

Prepared

Prepared By:	J Carlson
Date:	12/06/06

Emergency Contact Details

Emergency Contact:	1-800-255-3924 or Poison Center
Tel.Information:	(719) 676 3928
Address:	United Static Control Products.com Inc POB 19252, 4878 Lakeview Cir Colorado City, CO, 81019,USA

SECTION II - HAZARDOUS INGREDIENTS

Hazardous Components	PEL(ppm)	TWA(ppm)	STEL(ppm)	Other Limits	%(Opt)	CAS Reg#
-	-	-	-	-	-	-

Not a hazardous mixture, as defined in 29 CFR 1910,1200 and M.G.L. c. 111F

Contains: Glycol Ethers* <6

*Chemical category subject to reporting requirements of SCT.313 of TITLE III.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor	Translucent White Liquid
Auto Ignition Temp.	N.A
Boiling point	218 F
Decomposition Temperature	N.A
Evaporation Rate(Butyl Acetate=1)	0.36
Melting Point	N.A
pH	8.6 +/-0.4
Specific Gravity(Water=1)	1.02
Solubility in water	Complete
Vapor Pressure (mm Hg)	18
Vapor Density (air=1)	1.1
Viscosity (CPS)	15

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point	None
Extinguishing media	N.A
Fire Fighting Procedure	N.A
Fire and Explosion Hazards	N.A
Flammable Limits	LEL - N.A.,UEL - N.A.

SECTION V - REACTIVITY DATA

Stability	Stable
Conditions to Avoid	Freezing, Extreme Heat
Incompatibility	Acids, Oxidizers
Hazardous Decomposition or Byproduct	Thermal Decomposition may yeild CarbonMonoxide
Hazardous Polymerization	Will not occur
Conditions to Avoid	N.A

The information herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or results to be obtained from use thereof. Essentially similar to OSHA form # 174

SECTION VI - HEALTH HAZARD DATA

Routes of Entry	Inhalation	Skin	Ingestion
	No	No	No
Acute	Causes Eye and Skin Irritation		
Chronic	Redness of Skin		
Carcinogenicity	No		
NTP	N.A		
IARC Monographs	N.A		
OSHA Regulated	No		
Signs and Symptoms of Exposure	Irritation, Redness of Skin, Eyes		
Medical Conditions Aggravated	N.A		
Emergency and First Aid Procedures	Wash contact areas with soap and water. INGESTION:Drink milk, water, fruit juice, induce vomiting with oil of ipecac, get medical attention.		

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled
1. Dike, collect material into watertight container, rinse surface with clean water
Waste Disposal Method
1. Use sanitary landfill disposal, (not a hazardous waste) according to federal, state and local regulations. (RCRA, Subtitle D.)
Precautions to be Taken in Handling and Storage
1. Do not mix with other chemicals.
2. Store away from heat.
3. Keep from Freezing.
Other Precautions
1. Keep away from children.

SECTION VIII - CONTROL MEASURES

Respiratory Protection
Not required with normal use.
Ventilation
Local Exhaust - N.A.
Mechanical - N.A.
Special - N.A
Other - Assure fresh air culation.
Protective Gloves
Recommended: Rubber,Plastic

Eye Protection

Recommended: Safety Glasses, Goggles

Other Protection

N.A

Work/Hygienic Practices

1. Do not eat, drink next to material.
2. Wash hands/face after work.

SECTION IX - TRANSPORTATION 49 CFR

Unit Cont.

55,30,5,1 GAL. Plastic Cont

OSHA

Not Regulated

DOT

Not Regulated

UN

Not Regulated

Report Qty.(Lbs)

N.A

Labels

No

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Further more, vendee assumes the risk in use of the material.

[ESD Flooring](#) | [Mats](#) | [ESD Floor Care Products](#) | [ESD Ionizers](#) | [Ultrastat2000.com\(our original site\)](#)

Major Credit Cards Accepted

[TERMS CONDITIONS AND YOUR PRIVACY](#)

© 1996-2017 All rights Reserved

This site is protected by copyright and trademark laws under US and International law.

United Static Control Products Inc

4301 32nd Street West, Suite B20
 Bradenton, FL 34205
 United States of America