

This chemical is approved for use only on Copper Labs assemblies. It has an expiration date of April 15, 2020. It is not to be used on any new products.

Sarah Johnson

1-27-2020

<div>VERGENT</div> <div>PRODUCTS</div>	Procedure:		Revision:	Date of last Revision:	Owner:
	EHS – Hazard Assessment		C	02/13/2018	Director of Quality
	Description: Production line for Copper Labs product containing CPL-0000025				

Task	Hazard(s)	Engineered Controls	PPE		Emergency Response	Comments
			PPE	Required	Optional	
Apply two-part adhesive	(CEM)	VMS Checklist Adhesive is applied under Ventilation Hood	Apron	X		Procedure MUST be performed with product and adhesive inside the Ventilation Hood with the front panel down and the fan on.
			Safety Glasses Butyl Gloves Ventilation Hood	X X X X		
			Any person who is pregnant, may be pregnant or nursing shall not work these stations.	X		

VERGENT PRODUCTS	Procedure:		Revision:	Date of last Revision:	Owner:
	EHS – Hazard Assessment		C	02/13/2018	Director of Quality
	Description: Production line for Copper Labs product containing CPL-0000025				

Checklist:

- ☐ Procedural documentation updated. *List Change Order Number:* N/A Updated in pilot book
- ☐ Affected workers retrained to any new PPE requirements. *Date training took place:* _____
- ☐ Any new emergency response equipment or procedures in place. *List Change Order Number, Procedures or Equipment:* None

Review and Approval:

Author: I certify I am the author of this Hazard Assessment record.

Reviewer: I certify I am an authorized reviewer. I have reviewed and do hereby approve this Hazard Assessment record.

Approver: I certify I am an authorized approver. I have reviewed and do hereby approve this Hazard Assessment record.

	AUTHOR	REVIEWER	APPROVER
Printed Name	Keith Harral	Larry Schiferl	Sarah Johnson (Conditional*)
Signature	<i>Keith Harral</i>	<i>[Signature]</i>	<i>[Signature]</i>
Date	<i>1/21/2020</i>	<i>1-21-2020</i>	<i>1-21-2020</i>

* Approval is for a single job only and expires April 15, 2020. Concern: Cumene, a potential carcinogen and reproductive risk.



Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	08-6267-2	Version Number:	12.00
Issue Date:	08/11/17	Supersedes Date:	04/16/15

Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810 Tan

ID Number(s):

62-3298-1430-5, 62-3298-1431-3, 62-3298-1435-4, 62-3298-1436-2, 62-3298-3530-0, 62-3298-3830-4

Recommended use

Structural adhesive

Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

08-6252-4, 08-6239-1

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 08-6239-1

Issue Date: 05/21/18

Version Number: 21.00

Supersedes Date: 08/11/17

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810 Tan and Low Odor Acrylic Adhesive 810 Tan, Part B

Product Identification Numbers

62-3298-8730-1

1.2. Recommended use and restrictions on use

Recommended use

Structural adhesive

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes Division
International Operations

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark |

Pictograms

**Hazard Statements**

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

3% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Phenoxyethyl Methacrylate	10595-06-9	10 - 40 Trade Secret *
2-Hydroxyethyl Methacrylate	868-77-9	10 - 30 Trade Secret *
Hydroxypropyl Methacrylate	27813-02-1	10 - 30 Trade Secret *
Acrylate Oligomer	41637-38-1	5 - 20 Trade Secret *
Acrylonitrile-Butadiene Polymer	9010-81-5	5 - 20 Trade Secret *
2-Hydroxyethyl Methacrylate Phosphate	52628-03-2	< 4 Trade Secret *
4-Methoxyphenol	150-76-5	< 1 Trade Secret *
Phenothiazine	92-84-2	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions

on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
4-Methoxyphenol	150-76-5	ACGIH	TWA:5 mg/m3	
Phenothiazine	92-84-2	ACGIH	TWA:5 mg/m3	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Paste
Odor, Color, Grade:	slight fragrance, green
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	> 93 °C
Flash Point	> 200 °F [Test Method: Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	≤ 0.1 mmHg
Vapor Density	<i>No Data Available</i>
Density	1.07 g/ml
Specific Gravity	1.07 [Ref Std: WATER=1]
Solubility in Water	Slight (less than 10%)
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	20,000 centipoise
Hazardous Air Pollutants	< 40 % weight [Test Method: Calculated]
Molecular weight	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	3.1 g/l [Details: when used as intended with Part A]
VOC Less H2O & Exempt Solvents	0.3 % [Details: when used as intended with Part A]
VOC Less H2O & Exempt Solvents	319 g/l [Test Method: tested per EPA method 24] [Details: as supplied]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Amines

Reducing agents

Reactive metals

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg

Phenoxyethyl Methacrylate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Phenoxyethyl Methacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Acrylonitrile-Butadiene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Acrylate Oligomer	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Acrylate Oligomer	Ingestion	Rat	LD50 > 2,000 mg/kg
2-Hydroxyethyl Methacrylate Phosphate	Ingestion	Rat	LD50 > 2,000 mg/kg
4-Methoxyphenol	Dermal	Rat	LD50 > 2,000 mg/kg
4-Methoxyphenol	Ingestion	Rat	LD50 1,600 mg/kg
Phenothiazine	Dermal	Rat	LD50 > 2,000 mg/kg
Phenothiazine	Ingestion	Rat	LD50 1,370 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Phenoxyethyl Methacrylate	similar compounds	Irritant
2-Hydroxyethyl Methacrylate	Rabbit	Minimal irritation
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Minimal irritation
2-Hydroxyethyl Methacrylate Phosphate	Rabbit	Corrosive
4-Methoxyphenol	Rabbit	Mild irritant
Phenothiazine	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Phenoxyethyl Methacrylate	similar compounds	Severe irritant
2-Hydroxyethyl Methacrylate	Rabbit	Moderate irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
2-Hydroxyethyl Methacrylate Phosphate	similar health hazards	Corrosive
4-Methoxyphenol	Rabbit	Severe irritant
Phenothiazine	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
2-Hydroxyethyl Methacrylate	Human and animal	Sensitizing
Hydroxypropyl Methacrylate	Human and animal	Sensitizing
Acrylate Oligomer	Guinea	Not classified

	pig	
2-Hydroxyethyl Methacrylate Phosphate	Mouse	Sensitizing
4-Methoxyphenol	Guinea pig	Sensitizing
Phenothiazine	Guinea pig	Sensitizing

Photosensitization

Name	Species	Value
Phenothiazine	Human	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Phenoxyethyl Methacrylate	In Vitro	Not mutagenic
2-Hydroxyethyl Methacrylate	In vivo	Not mutagenic
2-Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydroxypropyl Methacrylate	In vivo	Not mutagenic
Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Acrylate Oligomer	In Vitro	Not mutagenic
2-Hydroxyethyl Methacrylate Phosphate	In Vitro	Not mutagenic
Phenothiazine	In Vitro	Not mutagenic
Phenothiazine	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hydroxypropyl Methacrylate	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
2-Hydroxyethyl Methacrylate Phosphate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Phenothiazine	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydroxypropyl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-Hydroxyethyl Methacrylate Phosphate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydroxypropyl Methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxypropyl Methacrylate	Ingestion	hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
2-Hydroxyethyl Methacrylate Phosphate	Ingestion	hematopoietic system kidney and/or bladder heart liver immune system eyes	Not classified	Rat	NOAEL 300 mg/kg/day	90 days
Phenothiazine	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Dog	NOAEL 18 mg/kg/day	13 weeks
Phenothiazine	Ingestion	heart endocrine system liver kidney and/or bladder respiratory system	Not classified	Dog	NOAEL 67 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative,

incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Phenoxyethyl Methacrylate (GLYCOL ETHERS)	10595-06-9	10 - 40

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 08-6239-1
Issue Date: 05/21/18

Version Number: 21.00
Supersedes Date: 08/11/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 08-6252-4
Issue Date: 05/21/18

Version Number: 17.00
Supersedes Date: 08/11/17

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810 Tan and Low Odor Acrylic Adhesive 810 Tan, Part A

Product Identification Numbers

62-3398-8730-9

1.2. Recommended use and restrictions on use

Recommended use

Structural adhesive

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Industrial Adhesives and Tapes Division
International Operations
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:

nervous system |

respiratory system |

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Phenoxyethyl Methacrylate	10595-06-9	10 - 40 Trade Secret *
2-Hydroxyethyl Methacrylate	868-77-9	10 - 30 Trade Secret *
Hydroxypropyl Methacrylate	27813-02-1	10 - 30 Trade Secret *
Acrylate Oligomer	41637-38-1	5 - 20 Trade Secret *
Acrylonitrile-Butadiene Polymer	9010-81-5	5 - 20 Trade Secret *

Cumene Hydroperoxide	80-15-9	1 - 5 Trade Secret *
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	< 1 Trade Secret *
Cumene	98-82-8	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Cumene Hydroperoxide	80-15-9	AIHA	TWA:6 mg/m3(1 ppm)	SKIN
Cumene	98-82-8	ACGIH	TWA:50 ppm	
Cumene	98-82-8	OSHA	TWA:245 mg/m3(50 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber
Fluoroelastomer

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

General Physical Form:	Liquid
Specific Physical Form:	Paste
Odor, Color, Grade:	white, low odor
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	>=217 °F
Flash Point	216 °F [<i>Test Method</i> :Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<=0.1 mmHg
Vapor Density	<i>Not Applicable</i>
Density	1.07 g/ml
Specific Gravity	1.07 [<i>Ref Std</i> :WATER=1]
Solubility in Water	Slight (less than 10%)
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	20,000 centipoise
Hazardous Air Pollutants	< 40 % weight [<i>Test Method</i> :Calculated]
Molecular weight	<i>No Data Available</i>
VOC Less H₂O & Exempt Solvents	3.1 g/l [<i>Details</i> :when used as intended with Part B]
VOC Less H₂O & Exempt Solvents	0.3 % [<i>Details</i> :when used as intended with Part B]

VOC Less H2O & Exempt Solvents

349 g/l [*Test Method*:tested per EPA method 24] [*Details*:as supplied]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Amines

Reducing agents

Reactive metals

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Cumene	98-82-8	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Cumene	98-82-8	Anticipated human carcinogen	National Toxicology Program Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Phenoxyethyl Methacrylate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Phenoxyethyl Methacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Acrylonitrile-Butadiene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Acrylate Oligomer	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Acrylate Oligomer	Ingestion	Rat	LD50 > 2,000 mg/kg

Cumene Hydroperoxide	Dermal	Rat	LD50 500 mg/kg
Cumene Hydroperoxide	Inhalation-Vapor (4 hours)	Rat	LC50 1.4 mg/l
Cumene Hydroperoxide	Ingestion	Rat	LD50 382 mg/kg
Cumene	Dermal	Rabbit	LD50 > 3,160 mg/kg
Cumene	Inhalation-Vapor (4 hours)	Rat	LC50 39.4 mg/l
Cumene	Ingestion	Rat	LD50 1,400 mg/kg
2,2'-Methylenebis[6-tert-butyl-p-cresol]	Dermal	Rabbit	LD50 > 10,000 mg/kg
2,2'-Methylenebis[6-tert-butyl-p-cresol]	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Phenoxyethyl Methacrylate	similar compounds	Irritant
2-Hydroxyethyl Methacrylate	Rabbit	Minimal irritation
Acrylonitrile-Butadiene Polymer	Professional judgment	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Minimal irritation
Cumene Hydroperoxide	Rabbit	Corrosive
Cumene	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Phenoxyethyl Methacrylate	similar compounds	Severe irritant
2-Hydroxyethyl Methacrylate	Rabbit	Moderate irritant
Acrylonitrile-Butadiene Polymer	Professional judgment	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
Cumene Hydroperoxide	Rabbit	Corrosive
Cumene	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
2-Hydroxyethyl Methacrylate	Human and animal	Sensitizing
Hydroxypropyl Methacrylate	Human and animal	Sensitizing
Acrylate Oligomer	Guinea pig	Not classified
Cumene	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

Phenoxyethyl Methacrylate	In Vitro	Not mutagenic
2-Hydroxyethyl Methacrylate	In vivo	Not mutagenic
2-Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydroxypropyl Methacrylate	In vivo	Not mutagenic
Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Acrylate Oligomer	In Vitro	Not mutagenic
Cumene Hydroperoxide	In vivo	Not mutagenic
Cumene Hydroperoxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cumene	In Vitro	Not mutagenic
Cumene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hydroxypropyl Methacrylate	Inhalation	Multiple animal species	Not carcinogenic
Cumene	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Cumene	Inhalation	Not classified for development	Rabbit	NOAEL 11.3 mg/l	during organogenesis
2,2'-Methylenebis[6-tert-butyl-p-cresol]	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	prematuring & during gestation
2,2'-Methylenebis[6-tert-butyl-p-cresol]	Ingestion	Toxic to male reproduction	Rat	NOAEL 12.5 mg/kg/day	50 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydroxypropyl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Cumene Hydroperoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Cumene Hydroperoxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Cumene Hydroperoxide	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	

		system depression	dizziness	nal judgement	available	
Cumene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
Cumene	Inhalation	respiratory irritation	May cause respiratory irritation	Human	LOAEL 0.2 mg/l	occupational exposure
Cumene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydroxypropyl Methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxypropyl Methacrylate	Ingestion	hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Cumene Hydroperoxide	Inhalation	nervous system respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	7 days
Cumene Hydroperoxide	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	90 days
Cumene	Inhalation	auditory system endocrine system hematopoietic system liver nervous system eyes	Not classified	Rat	NOAEL 59 mg/l	13 weeks
Cumene	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4.9 mg/l	13 weeks
Cumene	Inhalation	respiratory system	Not classified	Rat	NOAEL 59 mg/l	13 weeks
Cumene	Ingestion	kidney and/or bladder heart endocrine system hematopoietic system liver respiratory system	Not classified	Rat	NOAEL 769 mg/kg/day	6 months

Aspiration Hazard

Name	Value
Cumene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Cumene Hydroperoxide	80-15-9	Trade Secret 1 - 5
Phenoxyethyl Methacrylate (GLYCOL ETHERS)	10595-06-9	10 - 40

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 08-6252-4
Issue Date: 05/21/18

Version Number: 17.00
Supersedes Date: 08/11/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com