



Revision Number: 005.1

Issue date: 04/25/2022

1. PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|-------------------------------|--|---------------------|---------------|
| Product name: | LOCTITE EA 9394 AERO PART A QT | IDH number: | 937059 |
| Product type/use: | Adhesive for the Aerospace Industry | Item number: | AA9277016 |
| Restriction of Use: | None identified | Region: | United States |
| Company address: | Contact information: | | |
| Henkel Corporation | Telephone: +1 (860) 571-5100 | | |
| One Henkel Way | MEDICAL EMERGENCY Phone: Poison Control Center | | |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711 | | |
| | TRANSPORT EMERGENCY Phone: CHEMTREC | | |
| | 1-800-424-9300 (toll free) or 1-703-527-3887 | | |
| | Internet: www.henkelna.com | | |

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SKIN SENSITIZATION | 1 |



Precautionary Statements

| | |
|--------------------|--|
| Prevention: | Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. |
| Response: | IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| Storage: | Not prescribed |
| Disposal: | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations. |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|--|------------|-------------|
| Aluminum | 7429-90-5 | 30 - 40 |
| Tetraglycidyl diaminodiphenylmethane | 28768-32-3 | 30 - 40 |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | 25068-38-6 | 20 - 30 |
| Modified epoxy resin | Unknown | 5 - 10 |
| Treated fumed silica | 67762-90-7 | 1 - 5 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

| | |
|----------------------------|--|
| Inhalation: | If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention. |
| Skin contact: | Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention. |
| Eye contact: | In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention. |
| Ingestion: | Get medical attention. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions. |
| Symptoms: | See Section 11. |
| Notes to physician: | Treat symptomatically and supportively. |

5. FIRE FIGHTING MEASURES

| | |
|---|--|
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. |
| Special firefighting procedures: | Wear full protective clothing. Wear self-contained breathing apparatus. |
| Unusual fire or explosion hazards: | May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses. |
| Hazardous combustion products: | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| | |
|-----------------------------------|---|
| Environmental precautions: | Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways. |
| Clean-up methods: | Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations. |

7. HANDLING AND STORAGE

| | |
|------------------|--|
| Handling: | Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Do not heat Part A at temperatures greater than 80 °C (176 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. |
| Storage: | Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|--|--|---|-----------|-------|
| Aluminum | 1 mg/m3 TWA Respirable fraction. | 15 mg/m3 PEL (as Al) Total dust. 5 mg/m3 PEL (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. | None | None |
| Tetraglycidyl diaminodiphenylmethane | None | None | None | None |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | None | None | None | None |
| Modified epoxy resin | None | None | None | None |
| Treated fumed silica | 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. | 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. | None | None |

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Physical state: | Solid |
| Color: | Gray |
| Odor: | Mild |
| Odor threshold: | Not available. |
| pH: | Neutral |
| Vapor pressure: | Nil |
| Boiling point/range: | Not determined |
| Melting point/ range: | Not determined |
| Specific gravity: | 1.49 |
| Vapor density: | > 1 |
| Flash point: | > 93 °C (> 199.4 °F) |
| Flammable/Explosive limits - lower: | Not determined |
| Flammable/Explosive limits - upper: | Not determined |
| Autoignition temperature: | Not determined |
| Flammability: | Not applicable |
| Evaporation rate: | Not determined |
| Solubility in water: | Negligible |
| Partition coefficient (n-octanol/water): | Not determined |
| VOC content: | < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated) |
| Viscosity: | Not available. |
| Decomposition temperature: | > 200 °C |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Stability: | Stable at normal conditions. |
| Hazardous reactions: | May occur. |
| Hazardous decomposition products: | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen. |
| Incompatible materials: | Strong acids and oxidizing agents. Amines. |
| Reactivity: | Not available. |
| Conditions to avoid: | To avoid thermal decomposition, do not overheat. |

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

| | |
|----------------------|---|
| Inhalation: | May cause nose, throat and lung irritation. |
| Skin contact: | Causes skin irritation. May cause allergic skin reaction. |
| Eye contact: | Causes serious eye irritation. |
| Ingestion: | May be harmful if swallowed. |

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|--|--|---|
| Aluminum | Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l | Central nervous system, Irritant, Lung |
| Tetraglycidyl diaminodiphenylmethane | Inhalation LC50 (Rat, 4 h) = > 30 mg/m3 | Allergen, Blood, Central nervous system, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Nervous System |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | None | Allergen, Irritant |
| Modified epoxy resin | None | No Data |
| Treated fumed silica | None | Irritant |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| Aluminum | No | No | No |
| Tetraglycidyl diaminodiphenylmethane | No | No | No |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | No | No | No |
| Modified epoxy resin | No | No | No |
| Treated fumed silica | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Tetraglycidyl diaminodiphenylmethane, Bisphenol-A Epichlorhydrin resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetraglycidyl diaminodiphenylmethane, Bisphenol-A Epichlorhydrin resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III
Marine pollutant: Tetraglycidyl diaminodiphenylmethane, Bisphenol-A Epichlorhydrin resin
Exceptions: Classified per IMDG Amendment 34; Effective Jan 1, 2010.

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Propylene oxide (CAS# 75-56-9). Epichlorhydrin (CAS# 106-89-8). Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Aluminum (CAS# 7429-90-5).
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 12

Prepared by: Regulatory Affairs

Issue date: 04/25/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.